## TObject

| | | |
|---|---|---|
| fUniqueID | kIsReferenced | kZombie |
| fBits | kHasUUID | kBitMask |
| fgDtorOnly | kCannotPick | kSingleKey |
| fgObjectStat | kNoContextMenu | kOverwrite |
| kCanDelete | kInvalidObject | kWriteDelete |
| kMustCleanup | kIsOnHeap | fgIsA |
| kObjInCanvas | kNotDeleted | |

| | | |
|---|---|---|
| @~TObject | GetObjectInfo | operator new@[@] |
| MakeZombie | GetTitle | operator delete |
| DoError | HandleTimer | operator delete@[@] |
| TObject | Hash | operator delete |
| TObject | InheritsFrom | operator delete@[@] |
| operator= | InheritsFrom | SetBit |
| AppendPad | Inspect | SetBit |
| Browse | IsFolder | ResetBit |
| ClassName | IsEqual | TestBit |
| Clear | IsSortable | TestBits |
| Clone | IsOnHeap | InvertBit |
| Compare | IsZombie | Info |
| Copy | Notify | Warning |
| Delete | Is | Error |
| DistancetoPrimitive | Paint | SysError |
| Draw | Pop | Fatal |
| DrawClass | Print | AbstractMethod |
| DrawClone | Read | MayNotUse |
| Dump | RecursiveRemove | Obsolete |
| Execute | SaveAs | GetDtorOnly |
| Execute | SavePrimitive | SetDtorOnly |
| ExecuteEvent | SetDrawOption | GetObjectStat |
| FindObject | SetUniqueID | SetObjectStat |
| FindObject | UseCurrentStyle | Class |
| GetDrawOption | Write | Class_Name |
| GetUniqueID | Write | IsA |
| GetName | operator new | ShowMembers |
| GetIconName | operator new@[@] | |
| GetOption | operator new | |

## AliMUONPainterDataRegistry

| |
|---|
| fgInstance |
| fDataMakers |
| fZombies |
| fInteractiveReadOutConfig |
| fgIsA |

| |
|---|
| @~AliMUONPainterDataRegistry |
| DataMaker |
| DataSource |
| DataSource |
| InteractiveReadOutConfig |
| DataSourceWasRegistered |
| DataSourceWasUnregistered |
| DataMakerWasRegistered |
| DataMakerWasUnregistered |
| Instance |
| NumberOfDataMakers |
| NumberOfDataSources |
| Print |
| Register |
| Unregister |
| DeleteZombies |
| AliMUONPainterDataRegistry |
| AliMUONPainterDataRegistry |
| operator= |
| CreateInteractiveReadOutConfig |
| Class |
| Class_Name |
| IsA |
| ShowMembers |

## TQObject

| |
|---|
| fListOfSignals |
| fListOfConnections |
| fSignalsBlocked |
| fgAllSignalsBlocked |
| fgIsA |

| |
|---|
| @~TQObject |
| GetSender |
| GetSenderClassName |
| ConnectToClass |
| ConnectToClass |
| CheckConnectArgs |
| TQObject |
| operator= |
| TQObject |
| GetListOfClassSignals |
| GetListOfSignals |
| GetListOfConnections |
| AreSignalsBlocked |
| BlockSignals |
| CollectClassSignalLists |
| EmitVA |
| EmitVA |
| Emit |
| Emit |
| Emit |
| Emit |
| Emit |
| Emit |
| Emit |
| Emit |
| Emit |